



D08 Common Rail

Type	Cylinders	Swept volume cm ³	Rated output kW (hp), min ⁻¹	Max. torque Nm, min ⁻¹	Exhaust-gas cleaning	Exhaust-gas	
						standard	Euro
D0834 LFL	4	4,580	110 (150), 2,400	570 / 1,400	MAN PM-KAT®	4	
D0834 LOH / LFL	4	4,580	132 (180), 2,400	700 / 1,400	MAN PM-KAT®	4	
D0834 LOH / LFL	4	4,580	151 (206), 2,400	830 / 1,400	MAN PM-KAT®	4	
D0836 LOH / LFL	6	6,871	176 (240), 2,300	925 / 1,200 –1,800	MAN PM-KAT® *	4	
D0836 LOH / LFL	6	6,871	206 (280), 2,300	1,100 / 1,200 –1,620 / 1,800	MAN PM-KAT® *	4	
D0836 LFL	6	6,871	240 (326), 2,300	1,250 / 1,200 –1,800	MAN PM-KAT®	4	

*LOH = vertical, for buses
LF = vertical, for trucks*

** LOH with CRT filter system on request*

D20 Common Rail

Type	Cylinders	Swept volume cm ³	Rated output kW (hp), min ⁻¹	Max. torque Nm, min ⁻¹	Exhaust-gas cleaning	Exhaust-gas	
						standard	Euro
D2066 LOH / LF	6	10,520	235 (320), 1,900	1,600 / 1,000 –1,400	MAN PM-KAT® *	4	
D2066 LOH / LF	6	10,520	265 (360), 1,900	1,800 / 1,000 –1,400	MAN PM-KAT® *	4	
D2066 LOH / LF	6	10,520	294 (400), 1,900	1,900 / 1,000 –1,400	MAN PM-KAT®	4	
D2066 LOH / LF	6	10,520	324 (440), 1,900	2,100 / 1,000 –1,400	MAN PM-KAT®	4	
D2066 LUH	6	10,520	199 (270), 1,900	1,250 / 1,000 –1,400	MAN PM-KAT® *	4	
D2066 LUH	6	10,520	228 (310), 1,700	1,550 / 1,000 –1,400	MAN PM-KAT® *	4	
D2066 LUH	6	10,520	257 (350), 1,700	1,750 / 1,000 –1,400	MAN PM-KAT® *	4	
D2066 LUH	6	10,520	287 (390), 1,700	1,900 / 1,000 –1,400	MAN PM-KAT®	4	
D2066 LUH	6	10,520	316 (430), 1,700	2,100 / 1,000 –1,400	MAN PM-KAT®	4	
D2066 LF	6	10,520	294 (400), 1,900	1,900 / 1,000 –1,400	MAN AdBlue®	5	
D2066 LF	6	10,520	324 (440), 1,900	2,100 / 1,000 –1,400	MAN AdBlue®	5	

*LOH = vertical, for buses
LUH = horizontal, for buses
LF = vertical, for trucks*

** with CRT filter system on request*

D26 Common Rail

Type	Cylinders	Swept volume cm ³	Rated output kW (hp), min ⁻¹	Max. torque Nm, min ⁻¹	Exhaust-gas cleaning	Exhaust-gas	
						standard	Euro
D2676 LOH	6	12,412	338 (460), 1,900	2,100 / 1,050 –1,400	MAN PM-KAT®	4	
D2676 LOH / LF	6	12,412	353 (480), 1,900	2,300 / 1,050 –1,400	MAN PM-KAT®	4	
D2676 LF	6	12,412	353 (480), 1,900	2,300 / 1,100 –1,400	MAN AdBlue®	5	
D2676 LF	6	12,412	397 (540), 1,900	2,500 / 1,100 –1,400	MAN AdBlue®	5	

*LOH = vertical, for buses
LF = vertical, for trucks*